

昆阁林五金（昆山）有限公司

BO

D
d
L₀
R

10%
LONG LIFE DEFL. DEFLESSION PER LUNGA DURATA

13.5%
AVERAGE WORKING DEFL. DEFLESSION MEDIA DI LAVORO

15%
MAX WORKING DEFL. DEFLESSION MAX DI LAVORO

CTLG. NR. CODICE	HOUSING SEDE Ø mm	ROD SPINA Ø mm	FREE LENGTH LUNGH. LIBERA mm	RATE RIGIDITÀ N/mm	DEFLECTION DEFLESSIONE mm	LOAD CARICO N	DEFLECTION DEFLESSIONE mm	LOAD CARICO N	DEFLECTION DEFLESSIONE mm	LOAD CARICO N	NR. PCS NR. PEZZI	
BO 10025	10	5	25	167	2.5	418	3.3	551	3.8	626	100	
BO 10032			32	130	3.2	416	4.3	559	4.8	624	100	
BO 10038			38	105	3.8	399	5.1	536	5.7	599	100	
BO 10044			WIRE SECTION SEZIONE FILO 2.2 x 2.7	44	86	4.4	378	5.9	507	6.6	568	100
BO 10051				51	79	5.1	403	6.9	545	7.7	604	50
BO 10064				64	62	6.4	397	8.6	533	9.6	595	50
BO 10076				76	51	7.6	388	10.3	525	11.4	581	50
BO 13025	12.5	6.3	25	288	2.5	720	3.3	950	3.75	1080	100	
BO 13032			32	216	3.2	691	4.3	929	4.8	1037	100	
BO 13038			38	176	3.8	669	5.1	898	5.7	1003	100	
BO 13044			44	149	4.4	656	5.9	879	6.6	983	100	
BO 13051			WIRE SECTION SEZIONE FILO 2.8 x 3.4	51	128	5.1	653	6.9	883	7.7	979	50
BO 13064				64	100	6.4	640	8.6	860	9.6	960	50
BO 13076				76	84	7.6	638	10.3	865	11.4	958	50
BO 13089	89	71		8.9	632	12.0	852	13.4	948	50		
BO 13102	102	61	10.2	622	13.8	842	15.3	933	50			
BO 16032	16	8	32	449	3.2	1437	4.3	1931	4.8	2155	100	
BO 16038			38	363	3.8	1379	5.1	1851	5.7	2069	100	
BO 16044			44	309	4.4	1360	5.9	1823	6.6	2039	100	
BO 16051			51	256	5.1	1306	6.9	1766	7.7	1958	100	
BO 16064			64	203	6.4	1299	8.6	1746	9.6	1949	50	
BO 16076			76	166	7.6	1262	10.3	1710	11.4	1892	50	
BO 16089			WIRE SECTION SEZIONE FILO 3.5 x 4.6	89	139	8.9	1237	12.0	1668	13.4	1856	50
BO 16102				102	114	10.2	1163	13.8	1573	15.3	1744	50
BO 16115				115	105	11.5	1208	15.5	1628	17.2	1811	50
BO 16127				127	94	12.7	1194	17.1	1607	19.1	1791	20
BO 16152	152	69	15.2	1049	20.5	1415	22.8	1573	20			
BO 16305	305	37	30.5	1129	41.2	1524	45.8	1693	20			
BO 19044	20	10	44	452	4.4	1989	5.9	2667	6.6	2983	50	
BO 19051			51	378	5.1	1928	6.9	2608	7.7	2892	50	
BO 19064			64	301	6.4	1926	8.6	2589	9.6	2890	50	
BO 19076			76	247	7.6	1877	10.3	2544	11.4	2816	20	
BO 19089			89	208	8.9	1851	12.0	2496	13.4	2777	20	
BO 19102			WIRE SECTION SEZIONE FILO 4.05 x 5.9	102	188	10.2	1918	13.8	2594	15.3	2876	20
BO 19115				115	159	11.5	1829	15.5	2465	17.2	2743	20
BO 19127				127	146	12.7	1854	17.1	2497	19.1	2781	20
BO 19152				152	121	15.2	1839	20.5	2481	22.8	2759	20
BO 19305				305	60	30.5	1830	41.2	2472	45.8	2745	10
BO 25044	25	12.5	44	1158	4.4	5095	5.9	6832	6.6	7643	50	
BO 25051			51	933	5.1	4758	6.9	6438	7.7	7137	50	
BO 25064			64	730	6.4	4672	8.6	6278	9.6	7008	50	
BO 25076			76	556	7.6	4226	10.3	5727	11.4	6338	20	
BO 25089			89	462	8.9	4112	12.0	5544	13.4	6168	20	
BO 25102			WIRE SECTION SEZIONE FILO 5.7 x 7.4	102	390	10.2	3978	13.8	5382	15.3	5967	20
BO 25115				115	360	11.5	4140	15.5	5580	17.2	6210	20
BO 25127				127	326	12.7	4140	17.1	5575	19.05	6210	10
BO 25152				152	255	15.2	3876	20.5	5228	22.8	5814	10
BO 25178				178	230	17.8	4094	24.0	5520	26.7	6141	10
BO 25203	203	202	20.3	4101	27.4	5535	30.4	6151	10			
BO 25305	305	136	30.5	4148	41.2	5600	45.8	6222	5			

SUPER HEAVY LOAD / CARICO SUPER FORTE

昆阁林五金（昆山）有限公司

BO

D
d
L₀
R

10%
 LONG LIFE DEFECTION
 DEFESSIONE PER
 LUNGA DURATA

13.5%
 AVERAGE WORKING DEFL.
 DEFESSIONE MEDIA
 DI LAVORO

15%
 MAX WORKING DEFL.
 DEFESSIONE MAX
 DI LAVORO


CTLG. NR. CODICE	HOUSING SEDE Ø mm	ROD SPINA Ø mm	FREE LENGTH LUNGH. LIBERA mm	RATE RIGIDITÀ N/mm	DEFLECTION DEFESSIONE mm	LOAD CARICO N	DEFLECTION DEFESSIONE mm	LOAD CARICO N	DEFLECTION DEFESSIONE mm	LOAD CARICO N	NR. PCS NR. PEZZI		
BO 32044	32	16	44	1300	4.4	5720	5.9	7670	6.6	8580	20		
BO 32051			51	1150	5.1	5865	6.9	7935	7.7	8798	20		
BO 32064			64	887	6.4	5677	8.6	7628	9.6	8515	20		
BO 32076			76	733	7.6	5571	10.3	7550	11.4	8356	20		
BO 32089			89	612	8.9	5447	12.0	7344	13.4	8170	20		
BO 32102			102	544	10.2	5549	13.8	7507	15.3	8323	20		
BO 32115			WIRE SECTION SEZIONE FILO 7.4 x 8.8	115	494	11.5	5681	15.5	7657	17.2	8522	10	
BO 32127				127	432	12.7	5486	17.1	7387	19.1	8230	10	
BO 32152				152	356	15.2	5411	20.5	7298	22.8	8117	10	
BO 32178				178	304	17.8	5411	24.0	7296	26.7	8117	10	
BO 32203				203	265	20.3	5380	27.4	7261	30.4	8069	10	
BO 32254				254	214	25.4	5436	34.3	7340	38.1	8153	5	
BO 32305				305	177	30.5	5399	41.2	7292	45.8	8098	5	
BO 38064				40	20	64	1228	6.4	7859	8.6	10561	9.6	11789
BO 38076			76			1017	7.6	7729	10.2	10373	11.4	11594	20
BO 38089			89			880	8.9	7832	12.0	10560	13.4	11748	20
BO 38102	102	762	10.2			7772	13.8	10516	15.3	11659	20		
BO 38115	115	679	11.5			7809	15.5	10525	17.3	11713	10		
BO 38127	WIRE SECTION SEZIONE FILO 8.4 x 10.9	127	622			12.7	7899	17.1	10636	19.1	11849	10	
BO 38152		152	509			15.2	7737	20.5	10435	22.8	11605	10	
BO 38178		178	429			17.8	7636	24.0	10296	26.7	11454	10	
BO 38203		203	374			20.3	7592	27.4	10248	30.4	11388	5	
BO 38254		254	296			25.4	7518	34.3	10153	38.1	11278	5	
BO 38305	305	246	30.5	7503	41.2	10135	45.8	11255	5				
BO 50064	50	25	64	1980	6.4	12672	8.6	17028	9.6	19008	20		
BO 50076			76	1811	7.6	13764	10.2	18472	11.4	20645	20		
BO 50089			89	1410	8.9	12549	12.0	16920	13.4	18824	10		
BO 50102			102	1215	10.2	12393	13.8	16767	15.3	18590	10		
BO 50115			115	1076	11.5	12374	15.5	16678	17.3	18561	10		
BO 50127			WIRE SECTION SEZIONE FILO 11.8 x 13.4	127	968	12.7	12294	17.1	16553	19.1	18440	10	
BO 50152				152	806	15.2	12251	20.5	16523	22.8	18377	10	
BO 50178				178	698	17.8	12424	24.0	16752	26.7	18637	5	
BO 50203				203	612	20.3	12424	27.4	16769	30.4	18635	5	
BO 50254				254	472	25.4	11989	34.3	16190	38.1	17983	5	
BO 50305				305	388	30.5	11834	41.2	15986	45.8	17751	5	
BO 63089			63	38	89	1517	8.9	13051	12.0	18204	13.4	20328	10
BO 63102	102	1295			10.2	13209	13.8	17871	15.3	19814	10		
BO 63115	115	1070			11.5	12305	15.5	16585	17.3	18458	10		
BO 63127	127	979			12.7	12433	17.1	16741	19.1	18650	10		
BO 63152	WIRE SECTION SEZIONE FILO 11.8 x 17.8	152			775	15.2	11780	20.5	15888	22.8	17670	10	
BO 63178		178			630	17.8	11214	24.0	15120	26.7	16821	5	
BO 63203		203			546	20.3	11084	27.4	14960	30.5	16626	5	
BO 63254		254			423	25.4	10744	34.3	14509	38.1	16116	5	
BO 63305	305	349	30.5	10645	41.2	14379	45.8	15967	5				

SUPER HEAVY LOAD / CARICO SUPER FORTE

BO

